


SMOOTHWALL

www.duraline.com



Customer Service
800-847-7661



FEATURES:

- Available from ½" to 16" diameters
- Manufactured from flexible HDPE, makes gradual bends without special equipment
- Continuous lengths reduce joining costs
- Excellent low temperature properties, allows installation in cold climates
- Outstanding long term cable protection from shifting ground, rock and root impingement
- Provides a permanent pathway, simplifies future cable repairs or replacment
- Available with UV protectant for aerial/lashed placement
- UL Listing Available from ½" - 6" for SDR 13.5, SCH 40 and SCH 80

INSTALLATION APPLICATION:

Existing Conduit, Plow, Direct Burial, Aerial

MARKET APPLICATION:




COLOR/STRIPE:



OPTIONS:

FOOTAGE MARKINGS Sequential foot or meter markings. Custom print streams available.

SILICORE™  SILICORE is co-extruded with the tough HDPE jacket creating a super, slick permanent lining. SILICORE lined ducts allow for higher speed cable jetting and longer cable pulls.

PREINSTALLED TAPE Factory pre-installed Bull-Line™ Pull Tape with EVEN-LOAD™, ensures extra slack at any access point throughout the reel. Available 500lb - 6,000lb tensile strength or locatable.

PREINSTALLED CABLE Specify single or multiple cables to be factory pre-installed.
Cable types: Service Drops, Fiber, Coaxial, 600Volt Al, 600 Volt Cu, Medium Voltage.